

Declaration of Performance

Nr. D300-02

1. **Product-type identification:** Dry-Pressed Ceramic Tiles, with water absorption $0,5\% < E_b \leq 3\%$
2. **Intended use:** For internal and external walls and flooring
3. **Manufacturer:** VitrA Karo Sanayi ve Ticaret A.Ş.
E-5 Karayolu Üzeri Şifa Mah. Hükümet Caddesi No.5
34941 Tuzla İstanbul -TÜRKİYE
4. **Authorised representative:** VitrA UK Limited
Park 34, Collett, Didcot OX11 7WB, United Kingdom
5. **System of assessment and verification of constancy performance:** System 4
6. **Declared performance:**

Essential characteristics	Performance	UK Designated technical specification
Reaction to fire	A1 / A1 _{FL}	BS EN 14411: 2012
Release of dangerous substance, for:		
- Cadmium	NPD / No Performance Determined	BS EN 14411: 2012
- Lead	NPD / No Performance Determined	BS EN 14411: 2012
- Other	NPD / No Performance Determined	BS EN 14411: 2012
Breaking strength	> 1100 N for thickness $\geq 7,5\text{mm}$ > 700 N for thickness $< 7,5\text{mm}$	BS EN 14411: 2012
Slipperiness -Tested according to BS 7976 (TRL/4S)	NPD / No Performance Determined	BS EN 14411: 2012
Tactility	NPD / No Performance Determined	BS EN 14411: 2012
Bond strength/adhesion for:		
- Cementitious adhesive, type C2	NPD / No Performance Determined	BS EN 14411: 2012
- Dispersion adhesive	NPD / No Performance Determined	BS EN 14411: 2012
- Reaction resin adhesive	NPD / No Performance Determined	BS EN 14411: 2012
- Mortar	NPD / No Performance Determined	BS EN 14411: 2012
Thermal shock resistance	Pass	BS EN 14411: 2012
Durability For:		
-Internal Use	Pass	BS EN 14411: 2012
-External Use: freeze-thaw resistance	Pass	BS EN 14411: 2012

7. The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Musa Yılmaz – Plant Director
Name and Function

BOZÜYÜK – 16/11/2021
Place and date of issue

Signature 