

**Declaration of Performance of Sanitary tapware - Electronic opening and closing sanitary tapware**

1. Unique identification code of the product type:

**Sanitary tapware - Electronic opening and closing sanitary tapware**

**General technical specification**

**See the list attached**

2. Product type, Batch or serial number or any other element allowing identification of the construction products as required under Article 11 (4) of the CPR:

**It is applicable;**

**for electrically operated (opening and closing) sanitary tapware used with sanitary appliances.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Personal Hygiene ( PH ) / Type 1**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required 11 ( 5 )

**Eczacıbaşı Building Materials ArtemA Faucet Division**

**4 Eylül Mah. Necmi Soylu Cd. No : 4**

**Bozüyük/BİLECİK**

**TURKEY**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Eczacıbaşı Building Materials - ARTEMA Faucet Division**

**4 Eylül Mah. Necmi Soylu Cad. No : 4**

**Bozüyük/BİLECİK**

**TURKEY**

**Tel : 00 90 228 314 07 90**

**Fax : 00 90 228 314 07 96**

**Email : [okan.barut@vitra.com.tr](mailto:okan.barut@vitra.com.tr)**

**<http://vitraglobal.com/>**

6. System or systems of assessment and verification of consistency of performance of the construction product as set out in CPR, Annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard.

**TS EN 15091**

8. Declared performance:

**Declaration of Performance of Sanitary tapware - Electronic opening and closing  
sanitary tapware**

<b>Product : TS EN 15091</b>		
<b>Essantial Characteristics</b>	<b>Performance</b>	<b>Harmonised Technical Specification</b>
Dynamic Pressure	≥ 0,5 Bar - <b>Pass</b>	TS EN 15091 February, 2014
Static Pressure	≤ 10 Bar - <b>Pass</b>	
Temperature – Hot	≤ 90 °C - <b>Pass</b>	
<ul style="list-style-type: none"><li>The declared performance is linked to thenique identification code in the attached product serie list.</li></ul>		

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This decleration of performance is issued under the sole responsibility of the manufacturer identified in point

**Okan Deniz Barut**

Quality Assurance Asst. Specialist

**Mesut ÜNAL**

Quality Assurance Manager

**Place and Date of issue :**

Eczacıbaşı Building Materials VİTRA Faucet Division  
Bozüyük- BİLECİK/ TURKEY  
07.01.2021

**Declaration of Performance of Sanitary tapware - Electronic opening and closing  
sanitary tapware**

Ürün Kodu	Seri Adı	Tanım
A47020 XXX	AQUASEE	EN 15091
A47021 XXX	AQUASEE	EN 15091
A47043 XXX	AQUASEE	EN 15091
A47046 XXX	AQUASEE	EN 15091
A47060 XXX	AQUASEE	EN 15091
A47061 XXX	AQUASEE	EN 15091
A47062 XXX	AQUASEE	EN 15091
A47063 XXX	AQUASEE	EN 15091
A47064 XXX	AQUASEE	EN 15091
A47065 XXX	AQUASEE	EN 15091
A47068 XXX	AQUASEE	EN 15091
A47072 XXX	AQUASEE	EN 15091
A47076 XXX	AQUASEE	EN 15091
A47077 XXX	AQUASEE	EN 15091
A47078 XXX	AQUASEE	EN 15091
A47079 XXX	AQUASEE	EN 15091
A47080 XXX	AQUASEE	EN 15091
A47081 XXX	AQUASEE	EN 15091
A47101 XXX	AQUASEE	EN 15091
A47102 XXX	AQUASEE	EN 15091
A47103 XXX	AQUASEE	EN 15091
A47104 XXX	AQUASEE	EN 15091
A47105 XXX	AQUASEE	EN 15091
A47106 XXX	AQUASEE	EN 15091

**Declaration of Performance of Sanitary tapware - Electronic opening and closing  
sanitary tapware**

A47107 XXX	AQUASEE	EN 15091
------------	---------	----------